

## Appendix B Recycling/Disposal of Vehicle Fluids and Other Wastes

The information in this appendix was obtained from Ecology's Hazardous Waste Program. For a copy of "Hazardous Waste Services Directory", Publication #91-12S, Revised December 1994, call Ecology's Hazardous Waste and Toxic Reduction Program at (360) 407-6721.

Material	Recommended Management
<b>Antifreeze</b>	Store separately for resale. Separate ethylene glycol from propylene glycol for off-site recycling. If not recyclable, send to Treatment, Storage, and Disposal Facility (TSDF) for disposal.
<b>Batteries</b>	INTACT: Accumulate under cover prior to sale, deliver to recycler or, return to manufacturer. BROKEN: Accumulate acid from broken batteries in resistant containers with secondary containment. Send to TSDF for disposal.
<b>Brake fluid</b>	Accumulate in separate, marked, closed container. Do not mix with waste oil. Recycle.
<b>Fuel</b>	Store gasoline, and diesel separately for use or resale. Mixtures of diesel, gasoline, oil, and other fluids may not be recyclable and may require expensive disposal.
<b>Fuel filters</b>	Drain fluids for use as product. With approval of local landfill operator, dispose to dumpster, if needed.
<b>Oil filters</b>	Puncture the filter dome and drain it for 24 hours. Put oil drained from filters into a "USED OIL ONLY" container. Keep drained filters in a separate container marked "USED OIL FILTERS ONLY." Locate a scrap metal dealer who will pick up and recycle filters. With approval of local landfill operator, dispose of drained filters to dumpster.
<b>Paint</b>	Accumulate oil-based and water-based paints separately for use or resale. If not recyclable, send accumulations to TSDF for disposal.
<b>Power steering fluid</b>	Same as for used oils
<b>Shop towels/oily rags</b>	Use cloth towels that can be laundered and reused. Accumulate used shop towels in a closed container. Sign up with an industrial laundry service that can recycle your towels.
<b>Solvents</b>	Consider using less hazardous solvents or switching to a spray cabinet that doesn't use solvent. Accumulate solvents separately. Consider purchasing a solvent still and recycling solvent on site. Do not mix with used oil. Do not evaporate as a means of disposal.
<b>Transmission oil, differential and rear end fluids</b>	Accumulate in your "USED OIL ONLY" container. Arrange for pickup for off-site recycling.
<b>Used oils; including, crankcase oil, transmission oil, power steering fluid and differential/rear end oil</b>	Keep used oil in a separate container marked "USED OIL ONLY." Do not mix with brake fluid, or used antifreeze. Do not mix with any other waste if material will be burned for heating. Arrange for pickup for off-site recycling.
<b>Windshield washer fluid</b>	Accumulate separately for use or resale. Discharge to on-site sewage disposal, or, if acceptable by the local sewer authority, discharge to sanitary sewer.

