



NOTES:

1. Barricades shall meet the design criteria of MUTCD section 6F.68 for a Type 3 barricade, except that the colors of the stripes shall be retroreflective (Type IV or better) white and retroreflective (Type IV or better) red.
2. Barricade section shall extend to limits of the roadway surface relying on the least number of posts while still providing equidistant spacing in accordance with the above detail.
3. Sign sheet shall be bolted to (or integral to) the cross member using 5/8-inch galvanized bolts with fender washers. Securing hardware shall not consist of or include nails, lag bolts, or screws.
4. Panel material shall be high density polyethelene (HDPE), or approved equivalent such as #2 or better Douglas Fir (Untreated).

<p>DCS PUBLIC WORKS</p> <p>NA TACOMA POWER</p>	<p>REVIEWED BY <i>GMS</i></p> <p>ENVIRONMENTAL SERVICES</p> <p>NA TACOMA WATER</p>		<p>APPROVED FOR PUBLICATION</p> <p><i>[Signature]</i></p> <p>CITY ENGINEER</p> <p>4/1/14 DATE</p>	<p>CITY OF TACOMA</p> <p>PERMANENT ROADWAY TERMINUS TYPE 3 BARRICADE</p> <p>STANDARD PLAN NO. SU-35</p>
--	--	--	---	---